



**packaging**

## mortar repair tube

### 1. Product Name

ASH GROVE® Mortar Repair Tube  
Product Number: 415

### 2. Manufacturer

ASH GROVE PACKAGING GROUP  
10816 Executive Center Drive, Ste. 100  
Little Rock, AR 72211  
Phone: (888) 289.1117  
Fax: (501) 224.3882  
[www.ashgrovepkg.com](http://www.ashgrovepkg.com)

### 3. Product Description

ASH GROVE® Mortar Repair Tube is specifically designed for repairing, tuckpointing and sealing cracks and joints in mortar. Simply squeeze from the resealable squeeze tube into cracks and mortar joints in brick, block, stone or tile up to 3/8" thick. Non-shrinking, with excellent adhesive strength and water resistance to provide superior protection. Also may be used for sealing around windows and doors.

#### BASIC USE:

Recommended for repairing and sealing cracks and mortar joints in:

- Brick
- Block
- Stone
- Cinder Block
- Stucco
- Concrete

#### COMPOSITION & MATERIALS:

ASH GROVE® Mortar Repair Tube contains a premixed, ready to use latex caulk.

### 4. Advantages/Benefits

ASH GROVE® Mortar Repair Tube has several advantages including:

- Excellent adhesion, will not crack or crumble
- Forms a strong, weather resistant seal
- Remains flexible for added durability
- Dries to a textured gray finish
- Can be painted to match wall color
- Use for interior or exterior applications

### 5. Preparation

Remove all broken and loose concrete from the crack to be repaired to ensure strong bond with the material. Rigorously and thoroughly clean surface area with hot water and a stiff brush to remove grease, oil, paint, dust and any other foreign materials, leaving the surface saturated but free of standing water. For best results, use a pressure washer to clean the surface.



### 6. Placement

Remove cap and cut tip at an angle, allowing a 1/4" to 3/8" opening. Force a bead of caulk out of the ASH GROVE® Mortar Repair Tube into cracks up to 3/8" thick and 3/8" deep. For cracks over 1/4" thick, apply in layers of two or more beads. Allow each layer to dry for approximately 30 minutes between applications. When finished caulking place the cap back on the tube to reseal and to keep material fresh for next project.

### 7. Curing

Clean any excess caulk squeezed from the ASH GROVE® Mortar Repair Tube from the repair area with a damp cloth. Caulk can be tooled to even out the surface. Wait at least 24 hours before painting over the caulk using latex paint only.

For optimum performance, apply in dry weather above 40°F. Do not apply if rain is expected within 24 hours.

### 9. Limitations

ASH GROVE® Mortar Repair Tube is not recommended for repair of large cracks (more than 3/8" thick and deeper than 3/8").

Do not place if temperatures are expected to fall below 40°F within the next 24-hour period.

Only latex paint should be used when painting caulk to match wall color.

### 10. Coverage

Coverage will vary by the thickness of applications. One 5.5 oz. tube yields approximately 6 to 9 linear feet at 3/8" bead.

### 11. Warning

Do not take internally. If accidentally ingested, seek immediate medical attention. Normal safety wear such as protective clothing, boots, rubber gloves, dust masks, eye safety glasses should be worn while handling cement-based products. Material Safety Data Sheets are available upon request or at [www.ashgrovepkg.com](http://www.ashgrovepkg.com).

### 12. Limited Warranty

Packager, having no control over the use of the material, does not guarantee finished work. Replacement of any defective product or refund of the purchase price of defective product shall be the buyer's sole remedy under this warranty.

THIS LIMITED WARRANTY EXCLUDES ANY LIABILITY FOR ANY CONSEQUENTIAL, INCIDENTAL, INDIRECT OR SPECIAL DAMAGES.



mortar repair tube (cont.)

EXCEPT FOR THE LIMITED WARRANTY MADE ABOVE, PACKAGER SPECIFICALLY DISCLAIMS AND EXCLUDES ANY OTHER EXPRESS WARRANTY, ANY IMPLIED WARRANTY OF MERCHANTABILITY OF GOODS AND ANY IMPLIED WARRANTY OF FITNESS OF GOODS FOR ANY PARTICULAR PURPOSE.